

# AVAILABLE FOR LEASE

CONTACT: GREG SCHMID/RESIDCO 312-726-3441 schmid@residco.com

## EMD Model MP15DC Diesel Electric Switching Locomotives



### LOCOMOTIVE DIMENSIONS

Length over coupler  
pulling faces: .....48' 8"  
Distance between  
bolster centers: .....24' 2"  
Truck-rigid wheel base: .....9' 0"  
Width of operator's cab: .....10' 1/8"  
Height above rails: .....15' 0"  
Wheel diameter: .....40"

### LOCOMOTIVE SPECIFICATIONS

**Horsepower:** ..... 1500 HP  
**Engine:** ..... 12-645-E, 12 cylinder roots blown  
**Main Generator:** ..... D32U  
**Auxiliary Generator:** ..... 10 kW  
**Traction Motors:** ..... (4) EMD D77/78 direct current  
**Standard Gearing:** ..... 62:15 gear ratio  
**Number of Axles:** ..... Four (4)  
**Couplers** ..... Type E, standard length  
**Tractive Effort @ Min. Cont. Spd.:** ..... 46,800 lbs @ 9.3mph  
**Air Brake Equipment:** ..... 26L  
**Fuel Capacity:** ..... 1400 gallons  
**Approximate Loaded Weight:** ..... 248,000 lbs  
**Manufacturer:** ..... Electro-Motive Division GM  
**Remanufacturer:** ..... VMV  
**Dates Remanufactured:** ..... 1991  
**Retention Tank:** ..... Yes, external  
**Cab Heat:** ..... Electric